bagger-nielsen
we combine product, technique & knowhow

BN UNI-JACKET PRO

- flexible protection jacket for **UR3, 5 &10**

Close with velcro

BN UNI-JACKET PRO for UR3, 5 & UR10

Material Data Sheet Tyvek®
Surface weight: Approx. 43g/m2 ISO 536
Flexibility: 80,000 cycles ISO 7854
(PrEN1512) (method B)
Tear strength along: 24.6 N ISO 9073 ^ 4
Tear strength across: 29.1 N ISO 9073 ^ 4
• Temperature stability: -10° to + 70° C
• Water absorption: 0.05%
• oil- and petrol resistant
• acid and alkali resistant
free of substances which are not harmful to paint

Material Data Sheet Aramid-tissue
Technical Data: Para-Aramid A290
Weight: 290 g/m2 +/- 8%
Width: 1000 mm +/- 5%
Strength: 0,7 mm
Binding: Crossbones 3/1

Construction Technology:
Chain: 36 tex x 2 (28/2 Nm)
Shot: 70 tex K l (14/1 Nm)
Thread count chain: 230 fd/10 cm ± 10
Thread number shot; 150 fd/10 cm ± 10

Construction:
Chain; 4000 N / 5 cm - Shot: 1000 N / 5cm

Flame retardant, one sided gray special coating
Application temperature: - Raw fabric approx. 300° C
- coating approx. 200° C
Free of substances which are not harmful to paint