

UNI Ex Dicht-Kabelverschraubung

UNI Ex Dicht cable gland



Abb. 1
Fig. 1

Abb. 2
Fig. 2

Edelstahl VA 1.4305
Metrisches Anschlussgewinde EN 60423
Mit O-Ring Silikon
Schutzart IP 66, IP 68 bis 10 bar

Stainless steel AISI 303
Metric connection thread EN 60423
With o-ring silicone
Type of protection IP 66, IP 68 up to 10 bar

i Gewinde-Varianten: Standard-Maß D = Art.-Nr. 22052...
Thread variants: 15 mm Länge = Art.-Nr. 82052...
Standard size D = art. no. 22052...
15 mm length = art. no. 82052...

Werkstoff Verschraubungskörper Material gland body	Ausführung/Farbe Version/colour	Bestellschlüssel Art. no. supplement	Werkstoff Dichteinsatz Material sealing insert	Farbe Colour	Temperaturbereich min./max. Temperature range (min./max.)
VA 1.4305 AISI 303	Blank	st	TPE	s. FC s. CC	-20 °C / +60 °C




Abb. 3
Fig. 3

Anschlussgewinde/-länge Connection thread/length A	D mm	Art.-Nr. Art. no.	Dichtbereich Sealing range max./min. ø mm	Bauhöhe Mounting height C mm	Schlüsselweite Spanner width SW ₁ x E ₁ /SW ₂ x E ₂ mm	
M10x1,0	5,0	21049st7ex-12/1	6,5– 5,0	20,0	14x15,5	50
M12x1,5	5,0	21249st7ex-12	6,5– 5,0	20,0	14x15,5	50
M16x1,5	6,0	21650st7ex-12	6,5– 5,0	20,0	19x21/17x18,9	50
		21650st8ex-12	8,0– 6,0	20,0	19x21/17x18,9	50
		21650st9ex-12	9,5– 7,5	20,0	19x21/17x18,9	50
M20x1,5	6,0	22051st7ex-12	6,5– 5,0	20,0	22x24,4/20x22,2	50
		22051st8ex-12	8,0– 6,0	20,0	22x24,4/20x22,2	50
M20x1,5	6,5	22052st7ex-12	6,5– 5,0	20,0	22x24,4	50
		22052st8ex-12	8,0– 6,0	20,0	22x24,4	50
		22052st9ex-12	9,5– 7,5	20,0	22x24,4	50
		22052st11ex-12	10,5– 8,0	20,0	22x24,4	50
		22052st13ex-12	13,0– 10,0	20,0	22x24,4	50
M25x1,5	7,5	22553st7ex-12	6,5– 5,0	21,0	27x30,5/24x26,7	50
		22553st8ex-12	8,0– 6,0	21,0	27x29,5/24x26,7	50
		22553st9ex-12	9,5– 7,5	21,0	27x29,5/24x26,7	50
		22553st11ex-12	10,5– 8,0	21,0	27x29,5/24x26,7	50
		22553st13ex-12	13,0– 10,0	21,0	27x29,5/24x26,7	50
M32x1,5	8,0	23254st11ex-12	10,5– 8,0	25,0	36x39,5/30x33,5	25
		23254st13ex-12	13,0– 10,0	25,0	36x39,5/30x33,5	25
		23254st16ex-12	15,5– 12,5	25,0	36x39,5/30x33,5	25
		23254st18ex-12	18,0– 15,0	25,0	36x39,5/30x33,5	25
		23254st20ex-12	20,5– 18,0	25,0	36x39,5/30x33,5	25
M40x1,5	8,0	24055st16ex-12	15,5– 12,5	25,0	46x51/41x45	10
		24055st18ex-12	18,0– 15,0	25,0	46x51/41x45	10
		24055st20ex-12	20,5– 18,0	25,0	46x51/41x45	10
		24055st25ex-12	25,0– 21,0	25,0	46x51/41x45	10
		24055st28ex-12	28,0– 25,0	25,0	46x51/41x45	10
M50x1,5	10,0	25056st32ex-12	32,0– 28,0	28,0	55x60,5/50x54	5
		25056st34ex-12	34,0– 30,0	28,0	55x60,5/50x54	5
		25056st36ex-12	36,0– 33,0	28,0	55x60,5/50x54	5
		25057st40ex-12	40,0– 37,0	30,0	60x65	5
M63x1,5	10,0	26358st44ex-12	44,0– 40,0	30,0	68x74/65x70	5

i Weitere Ausführungen auf Anfrage
Other versions on request

i Ausführung in Edelstahl V4A auf Anfrage
Stainless steel version AISI 316Ti on request