


TECHNICAL DATA SHEET

PMAFLEX Multilayer - XPCL - Corrugated Conduit

Very flexible, medium-duty

PMA



Very flexible conduit which allows easy cable insertion due to low friction inner layer



Applications:

- In machine building and equipment with high requirements

Features & Benefits:

- Very long life time, 15 - 20 years for standard applications
- Easy cable insertion, low friction inner layer impermeable to water and steam
- Very good flexibility
- Good mechanical strength even at low temperatures and low humidity
- Self-extinguishing

Materials:

- Outer layer: High-grade, specially formulated polyamide 6
- Intermediate layer: spec. bonding compound
- Inner layer: Specially modified polyethylene

Compatible with:

- PMAFIX Pro, PMAFIX fittings
- PMA accessories

Temperature range:

- -50°C ... +105°C continuous, +160°C short-term

Weathering resistance:

- Very good UV resistance and weathering characteristics, particularly in black

Colour:

- Outer layer: black or grey, other colours on request
- Inner layer: blue

Chemical properties:

- Please refer to www.pma.ch (Technical Information / Chemical Resistance)

Environmental properties:

- Free from halogens and cadmium
- RoHS and REACH compliant


XPCL-Index

	min.									max.
Ductility	[Progressive bar chart from min to max]									
Fatigue reversed bending	[Progressive bar chart from min to max]									
Compression resistance	[Progressive bar chart from min to max]									
Low temperature performance	[Progressive bar chart from min to max]									
Weathering resistance	[Progressive bar chart from min to max]									

Product selection:

Part no.		Profile	Conduit size		rec. fitting thread size		Dimensions in mm (nom.)			Weight	Packing unit
black	grey	T/G	NW	metric	PG	metric	d1	d2	stat. R	kg/100 m	metre
XPCLT-10BB	XPCLT-10SB	T	10	12	9	M12x1.5	9.6	12.8	20	3.0	50
XPCLT-12BB	XPCLT-12SB	T	12	16	11	M16x1.5	11.9	15.6	25	4.0	50
XPCLT-17BB	XPCLT-17SB	T	17	20	16	M20x1.5	16.5	21.1	35	6.0	50
XPCLG-17BB	XPCLG-17SB	G	17	20	16	M20x1.5	15.7	21.1	40	6.0	50
XPCLG-23BB	XPCLG-23SB	G	23	25	21	M25x1.5	21.9	28.4	50	9.5	50
XPCLG-29BB	XPCLG-29SB	G	29	32	29	M32x1.5	27.6	34.5	60	13.5	50
XPCLG-36BB	XPCLG-36SB	G	36	40	36	M40x1.5	36.0	42.4	75	16.0	30
XPCLG-48BB	XPCLG-48SB	G	48	50	48	M50x1.5	47.1	54.5	90	22.0	30

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



stat. R. = min. bending radius for static (fixed) installation

Mechanical Properties:	Value:	Test parameters:	Test method:
Impact strength	> 6 J	(+ 23°C)	PMA DO 9.21-4330
	> 12.2 J	(- 18°C)	CSA C22.2 Nr. 227.3 / UL 1696
Compression strength	> 150 N	(50 x 50 mm)	PMA DO 9.21-4320
	> 300 N	(100 x 100 mm)	PMA DO 9.21-4320
Reverse bending resistance	> 250'000 cycles		PMA DO 9.21-4420
	> 750'000 cycles		PMA DO 9.21-4425
Pull-out resistance conduit - fitting series			
PMAFIX Pro	> 350 N		PMA DO 9.21-4610
PMAFIX IP68	> 300 N		PMA DO 9.21-4610
PMAFIX IP66	> 270 N		PMA DO 9.21-4610
PMAFIX Pro, PMAFIX IP66 & IP68	class 2		IEC EN 61386

Note: Testing at 23°C, 50% r.h., conduit nominal width 17, unless otherwise stated

Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	-50 ... +105°C		PMA DO 9.21-4510
Upper application temperature	+120°C	(20'000 h)	PMA DO 9.21-4360
Short-term	+160°C	(168 h)	PMA DO 9.21-4360

Fire safety properties:	Value:	Test parameters:	Test method:
Fire performance	non flame-propagating		IEC EN 61386
Fire performance	V2		UL 94
Fire performance	compliant		UL 224

ABB Switzerland Ltd,
PMA Cable Protection
Aathalstrasse 90
8610 Uster, Switzerland
Phone: +41 58 585 00 11
pma-info@ch.abb.com
www.pma.ch

Let's write the future.
Together. **abb.com**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc. Copyright© 2019 ABB Installation Products Inc. All rights reserved

