
 TECHNICAL DATA SHEET

PMAFIX IP68 - BVNZ-P - Strain relief fitting

Straight, PG thread

PMA



IP68, polyamide thread strain relief fitting
for flexible non-metallic conduit



Applications:

- In machine and plant construction
- For separation of damp and dry areas

Features & Benefits:

- Very high impact resistance
- Vibration-proof connection to PMA conduits
- Easy installation
- High conduit pull-out strength
- Integrated strain relief optimally holds and seals cables
- If several conductors are used with the connector multiple sealing inserts should be considered
- Very good chemical properties
- Fits both conduit profiles - fine (T) and coarse (G)

Ingress protection:

- IP66, IP68 & IP69 (EN/IEC 60529)
- IP69, 100 bar with Water impact protection (WPS-ring)
- IP68 (up to 5 bar at the cable)

Materials:

- Fitting body: high-grade, specially formulated polyamide 6
- Gland body: polyamide 6
- Sealing insert: CR/NBR

Compatible with:

- PMAFLEX Pro Conduits
- PMAFLEX Multilayer Conduits
- PMAFLEX Conduits
- PMA Smart Line Conduits

Conforms to:

- EN 45545-2 HL3 (R23 & R23)
- NFPA 130
- UL 94 (V0)

Weathering resistance:

- Very good UV resistance and weathering characteristics, particularly in black

Colour:

- Black
- Grey

Chemical properties:

- Please refer to www.pma.ch
(Technical Information / Chemical Resistance)


Environmental properties:

- Free from halogens and cadmium
- RoHS and REACH compliant

Product selection:

Part no.		Thread size	Conduit size	Cable clamping range in mm	Dimensions in mm (nom.)					Weight	Packing unit
black	grey	PG	NW	K	g	L	d2	SW1	SW2	kg/100pcs	pcs/PU
BVNZ-P090S	SVNZ-P090S	9	10	4.0 - 8.0	7.5	56.0	21.5	19	19	1.5	50
BVNZ-P112S	SVNZ-P112S	11	12	5.0 - 10.0	8.0	60.5	24.0	22	22	1.8	50
BVNZ-P132S	SVNZ-P132S	13.5	12	6.0 - 12.0	9.0	62.0	27.0	24	24	1.8	50
BVNZ-P137S	SVNZ-P137S	13.5	17	6.0 - 12.0	9.0	69.0	30.0	24	24	2.7	50
BVNZ-P167S	SVNZ-P167S	16	17	10.0 - 14.0	10.0	72.0	30.0	27	27	2.7	50
BVNZ-P163S	SVNZ-P163S	16	23	10.0 - 14.0	10.0	79.0	38.0	27	27	4.1	30
BVNZ-P213S	SVNZ-P213S	21	23	13.0 - 18.0	11.0	82.0	39.0	33	36	4.1	30
BVNZ-P299S	SVNZ-P299S	29	29	18.0 - 25.0	11.0	85.0	46.5	42	42	5.3	20
BVNZ-P366S	SVNZ-P366S	36	36	22.0 - 32.0	13.0	112.0	60.0	53	55	9.2	20
BVNZ-P488S	SVNZ-P488S	48	48	34.0 - 44.0	14.0	112.0	76.0	65	70	14.2	10

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



Mechanical Properties:	Value:	Test parameters:	Test method:
Tensile modulus	1'200 ... 3'700 N/mm ²		ISO 527
Tensile strength	45 ... 65 N/mm ²		ISO 527
Notched bar impact test	4 ... 20 kJ/m ²		ISO 180/1C
Vibration and shock standard	Cat. 2		IEC 61373, IEC 60068-2-27 / -64

Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	- 50 ... + 105 °C		PMA DO 9.21-4510
Upper application temperature	+ 120°C	(20'000 h)	PMA DO 9.21-4360
Short-term	+ 160 °C	(168 h)	PMA DO 9.21-4360

Fire safety properties:	Value:	Test parameters:	Test method:
Fire performance	non flame-propagating		IEC EN 61386-1
Flame class	V0		UL 94

Fire hazard level	HL3		EN 45545-2 (R22)
Oxygen index	> 32 %		EN ISO 4589-2
Smoke density	< 150 Ds max.		EN ISO 5659-2 (25 kW/m ²)
Toxicity	< 0.75 CIT _{NLP}		NF X 70-100-1/-2: (600°C)

Fire hazard level	HL3		EN 45545-2 (R23)
Oxygen index	> 32 %		EN ISO 4589-2
Smoke density	< 300 Ds max.		EN ISO 5659-2 (25 kW/m ²)
Toxicity	< 1.5 CIT _{NLP}		NF X 70-100-1/-2: (600°C)

Fire performance NFPA 130:			NFPA 130
- Flammability	compliant		ASTM E 162
- Smoke density	compliant		ASTM E 662

Heat and visible smoke	26.00 MJ/kg		ASTM E 1354
Smoke emission toxicity	compliant		Bombardier SMP 800-C
Smoke emission toxicity	compliant		Boeing BSS 7239

Note: Fire safety properties only applicable for PMA raw material

Content of delivery:

- Fitting with strain relief insert,
- Conduit locking clip (OVN2)
- Thread gasket (SVN4)
- Conduit seal (NVN3)

Assembly instructions:

- Please consider the appropriate assembly instructions on www.pma.ch

ABB Switzerland Ltd,
PMA Cable Protection
Aathalstrasse 90
8610 Uster, Switzerland
Phone: +41 58 585 00 11
pma-info@ch.abb.com
www.pma.ch

Let's write the future.
Together. **abb.com**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc. Copyright© 2019 ABB Installation Products Inc. All rights reserved

