

UA1250 QT/ET0250

COMPACT TRIO



Opening variant	Stay variant	h _i [mm]	B _i [mm]	t [mm]	KR [mm]	Additional load ≤ [kg/m]	Cable- d _{max} [mm]	Travel length unsupported ≤ [m]	Travel length gliding/rolling ≤ [m]	Inner Distribution				
										TS0	TS1	TS2	TS3	
UA1250														
	020	17.5	30 - 50	25	28 - 100	4	14	1.6	60	•	-	-	-	
QT0250														
	030	17.6	30 - 50	25	28 - 100	4	14	1.6	60	•	•	-	-	
	040	17.6	30 - 50	25	28 - 100	4	14	1.6	-	•	•	-	-	
ET0250														
	030	16.5	30 - 50	25	28 - 100	4	13	1.6	60	•	-	-	-	
	040	16.5	30 - 50	25	28 - 100	4	13	1.6	-	•	-	-	-	

OUR CLASSICS IN NEW SMALL SIZE - FAST AND COMPACT FOR SMALL CABLE PACKAGES

Applications

- » Automation technology
- » Printers and plotters
- » Handlings
- » Assembly machines
- » ... and more

Features

- » compact size for small installation spaces
- » small pitch for smooth run
- » low vibration due to integrated damping
- » quietly operating
- » gliding surface for long service life
- » for unsupported applications
- » suitable for horizontal circular applications
- » Lateral wear surfaces
- » 1:1 exchange against the previous model without changing the machine



TSUBAKI KABELSCHLEPP GmbH
Daimlerstraße 2 | 57482 Wenden-Gerlingen
www.tsubaki-kabelschlepp.com

